

CABLE DRAWING

Habia Cable

Drawing Number 700041840	Revision No 00	Status Released	Phase Proposal for Production
Description B/1819 STW 10		Habia Inspection Plan (HIP) HIP-G-420	Page 1 of 1
Customer Product Number		Created by T. Nälsén	Approved by T. Nälsén
Customer Product Description		Creation Date 2012-05-13	Approval Date 2012-05-13

Technical Data	Values at +20° C	Unit
Conductor Resistance	Max 21	Ω/km
Insulation Resistance	Min 1500	MΩ x km
Test Voltage	5 min: 7.5	kV DC
Voltage Rating	600	V AC
Radiation Tolerance	10 ⁶	Gy
Weight	TBD	g / m
Temperature Rating	50 years, conductor temperature: 90	°C

RoHS Compliant.

All dimensions in mm, unless otherwise stated.

Pos	Description	Dimension	Overall Diameter	Remarks
1.	Tin-plated copper conductor Insulation of HFI 150	18 AWG t = 0.30	1.21 1.80	19 x 0.254
2.	Binder, Polyester			
3.	Braid of tin-plated copper	Diam: 0.127	8.5	Min 85% coverage
4.	Binder, non-woven polyester		8.7	
5.	Jacket of HFS 105 XL type B, Black	t = 1.20 mm	11.1	

Jacket marking with meter indication in contrasting colour, intervals of 1,0 m ±0,02 m:

Habia Cable - 700041840 - YYYY-Www - batchcode - L m

YYYY-Www to be replaced with year and week of manufacture.

Batch code to be replaced with manufacturers traceability code

L indicates continuous meter marking and is replaced with actual length.

